


### Forced Pilot Operated Valve Technical Specifications

- **Function:** 2W NC
- **Main Ports:** 1/2" BSP
- **Side Ports:** 1/4" BSP.
- **Orifice:** 12 mm
- **Pressure Range:** 0-4 bar
- **Flow Factor Kv (l/min):** 35
- **Fluid Temperature:** -10 +80 °C
- **Ambient Temperature:** -10 to +50 °C
- **Material in Contact with Fluid:** Aluminum, Brass, NBR, AISI 430F, AISI 304
- **Coil:** 230/50 8W

This publication contains proprietary information of GevaSol  
Do not use, or distribute this document without prior  
Authorization in writing from GevaSol.

Geva Sol by  
**Geva**



GENERAL TOLERANCES UNLESS OTHERWISE SPECIFIED:		WEIGHT (gr.):		NAME	DATE	SIGNATURE
UNI ISO 2768 - m		VOLUME (Cubic millimeter):		Yo.Ha	.	
f m c v		DRAWING NUMBER:		DESIGNER	.	
		<b>P7078-A001</b>		APPROVED	Ko.Po.	12/04/2010 <i>[Signature]</i>
SURFACE: ( )	SCALE:	DESCRIPTION:		APPROVED		
NEXT ASSEMBLY:	<b>1:2</b>	<b>GEVA-Z</b>		MATERIAL:		REV.:
SHEET: 1 OF 1	DO NOT SCALE DRAWING	PRODUCT:		FINISH:		<b>A3</b>
ALL DIMENSION IN MILLIMETERS		DEBURG & BREAK SHARP EDGES 0.1 MAX.				